

4K color in near-total darkness vandal ball turret IP camera DWC-MVD8WiATW / DWC-MPVD8WiATW



Summary

This NDAA-compliant MEGApix® IP camera provides 4K resolution at realtime 30fps. The camera features Star-Light Plus™ color in near-total darkness technology for quality video in any lighting conditions and a vari-focal auto-focus lens with motorized zoom. The vandal ball turret cameras are IP66-rated, eliminate IR reflections, offer easy angle adjustment for optimal image quality and easy access to the camera's control board from the base of the camera. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 4K 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- 2.7~13.5mm vari-focal p-iris lens with motorized zoom and auto-focus
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Smart DNR[™] 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Backlight compensation (BLC)
- Motion detection
- Two-way audio
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- Alarm sensor input and relay output
- Web server built-in
- PoE class 3 and DC12V
- UL listed
- NDAA compliant
- IP66 environmental-rated dust-tight and water-resistant
- IK 9-rated impact-resistant
- 5 year warranty


Accessories (Optional)



DWC-V1CNMW Corner mount DWC-VFJUNCW

Junction box





Specifications

IMAGE	
Image sensor	4K 1/2.8" CMOS sensor
Total pixels	3864(H) x 2228(V)
Active pixels	3840 (H) X 2160 (V)
Minimum scene illumination	0.09 lux (color) 0 lux (B/W)
S/N ratio	50dB
Video output	Local video output CVBS 1.0V p-p (75Ω), 4:3 aspect ratio
LENS	
Focal length	2.7~13.5mm, F1.4
Lens type	Vari-focal p-iris lens with motorized zoom and auto-focus
Horizontal Field of view (HFoV)	33.1°~90.3°
Vertical Field of view (VFoV)	18.9°~49°
IR distance	100ft range
Optical zoom	5x optical zoom
I/O	
Audio in / out	1/1
Audio compression	G.711
Alarm in / out	1/1
OPERATIONAL	
Intelligent Video Analytics	IVA: intrusion, line crossing, counting line, loitering, enter, exit, tampe (DWC-MVD8WiATW) IVA: object removed, tailgating, direction, stopped, appear, disap-
Shutter mode	pear, object left, logical rules, logical rules (DWC-MPVD8WiATW)
	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter Auto gain control	1/2,1/3,1/5,1/6,1/7.5, 1/10 Auto
Day and night 3D Digital Noise Reduction	Auto, day (color), night (B/W) Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR)	True WDR, 120dB
White balance	Yes
Privacy zones	16 programmable privacy masks
Backlight compensation (BLC)	Yes
Mirror and flip	Yes
Alarm notifications	Notifications via email, FTP, alarm output and SD card recording
Memory slot	Micro SD/SDHC/SDXC class 10 card (card not included)
NETWORK	
LAN	1000Base-T (1Gbps)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: QFHD, 2.1MP/1080p, 720p, VGA, D1, CIF H.264: QFHD, 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 2.1MP/1080p, 720p, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps ~ 10Mbps, multi-rate for preview and recording
Bitrate control	Multi-streaming CBR/VBR at H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIE
Security	HTTPS (TLS), IP filtering, 802.1x, digest authetication
ONVIF conformance	Yes
Web viewer	OS: Windows [®] , Mac [®] OS, Linux [®] Browser: IE, Chrome, Firefox
Video management software ENVIRONMENTAL	DW Spectrum* IPVMS
Operating temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Operating humidity	10-90% RH, (non-condensing)
IK rating	IK9 impact-resistant
IP rating	IP66-rated
Other certifications	UL listed, CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC12V, PoE IEEE 802.3af Class 3 (Adapter not included)
Power consumption	DC12V 12.4W PoE 14.9W
	POE 14.9VV
MECHANICAL	Aluminum vandal hall turrat hauring
Material	Aluminum vandal ball turret housing
Dimensions Weight	4.92" x 4.4" (125 x 112mm) 1.87 lbs (0.85 kg)
	1.07 ID3 (0.03 Kg)
Warranty	5 year warranty



:sales@digital-watchdog.com

DWC-VFCMW



:www.digital-watchdog.com