








Dimensions

unit: Inch (mm)













Summary

The MEGApix® Pano™ 21MP multi-sensor IP vandal camera produces 180° views at real-time 30fps. The camera supports advanced features such as H.264 codec and Smart DNR™ in an aluminum vandal housing with zero distortion anti-reflective glass. The 21MP camera does the work of many cameras from one installation, delivering both unprecedented wide views and details.

Features

- 4x 6.4MP 1/1.8" image sensor at real-time 30fps
- 21MP 180° panoramic view IP camera
- 4x 8.0mm fixed lens
- Fast frame rates: real-time 30fps at 21MP
- Zero distortion anti-reflective glass
- PoE injector included
- Dual codecs (H.264, MJPEG) with simultaneous dual-stream
- Two-way audio
- Easy image alignment and stitching
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- Alarm sensor input and relay output
- Web server built-in
- **UL** listed
- ONVIF conformant, profile S
- PoE+ high power and DC12V
- IP66 environmental-rated dust-tight and water-resistant
- 5 year warranty

Cessories (Optional)



DWC-V1CNM Corner mount bracket

DWC-PMB-WL

Pole mount

bracket



DWC-PZCM Ceiling mount



DVIF DWC-PZADP Adapter for parapet mount



DWC-PZWM Wall mount

DWC-PZPARAM Parapet mount (DWC-PZADP required. Purchased separately)

Specifications



	USTED
IMAGE	
Image sensor	4x 1/1.8" CMOS
Total pixels	4x 3096 (H) x 2080 (V)
Minimum scene illumination	0.16 lux (color)
S/N ratio	50dB
Maximum resolution	21MP (4x 5.3MP)
LENS	
Focal length	4x 8.0mm, F1.6
Lens type	Fixed lens
Field of view (FoV)	Over 180°
1/0	
Audio in/out and compression	1(1.0Vms, 3K ohm) input/1 output, G.711
Alarm in/out	1input/1output
OPERATIONAL	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Shutter mode	Auto, Manual, Anti-Flicker, Slow Shutter
Shutter speed	1/15 ~ 1/32000
Slow Shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W)
Smart DNR™ 3D digital noise	
reduction	3D DNR
White balance	Auto
Mirror and flip	Yes
Backlight compensation (BLC)	Yes
Privacy zones	16 programmable privacy masks
Alarm notifications	Email notifications, FTP, alarm output, SD card recordin
Memory slot	Micro SD/SDHC/SDXC class 10 card (not included)
NETWORK	
	1000Dana T/1China)
LAN	1000Base-T(1Gbps)
Video compression type	H.264, MJPEG
Resolution	Up to 12,384 (H) x 2080 (V) total pixels
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps ~ 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264 (controllable frame
	rate and bandwidth)
Streaming capability	3072x1728p30 + 640x360p7 with H.264 and MJPEG (u to 16 streaming)
IP.	IPv4
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPvI/v2/v3, (MIB-2), ONVIF
Consults	HTTPS (TLS), IP filtering, 802.1x, digest authentication
Security	(ID/PW)
ONVIF conformance	Yes
Mah viouer	OS: Windows® 7, Windows® 8, Windows® 10
Web viewer	Browser: IE, Chrome, Firefox
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F ~ 122°F (-22°C ~ 50°C)
Operating humidity	Less than 80% (non-condensing)
IP rating	IP66-rated
Other certifications	FCC, CE, ROHS, UL listed
ELECTRICAL	
LEEC INICAL	DC12V, PoE IEEE 802.3at PoE+ Class 4
Power requirement	(High power PoE injector included)
Power consumption	DC12V: 21.5W PoE IEEE802.3at Class4: 23.2W
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate lens cover
Dimensions	7.55" x 4.25" (192 x 108mm)
	4.4 lbs (2kg)
Weight	



Increase sales and profitability. Sign up and become a DW Channel Partner today!







: sales@digital-watchdog.com



: www.digital-watchdog.com

